



# DigiPoS 15" LCD Monitors

- Available with Touch Capabilities and MSR

*The DigiPoS Range of LCD* monitors have a rugged, flexible design which stands up to the harshest point of sale environments. The sleek DigiPoS 710A and 714A model are available with either ELO touch or MICRO touch and has a small, retail friendly footprint.

This monitor features resistive or capacitive touch capabilities which is the considered to be the most widely accepted format for the Retail POS industry and can be integrated with a MSR if required.

Designed with flexibility in mind, this LCD can be mounted for added space on the retail counter.



## ADVANTAGES

- o Economical and reliable
- o Up to 1024 x 768 resolution
- o Resistive or Capacitive touch
- o Responsive to the touch of fingernails, credit cards, gloved hands and bare fingers
- o Display angle adjustable from 0 to 60 degrees

# Specifications:

## DigiPoS 15" and 15.1" LCD Displays



### MODEL

### 710A

### 714MSR

<b>LCD Display</b>	15" TFT Active Matrix Panel	15" TFT Active Matrix Panel
<b>Display Size</b>	304.1 x 228.1 mm	304.1 x 228.1 mm
<b>Pixel Pitch</b>	0.297 x 0.297 mm	0.297 x 0.297 mm
<b>Display Mode</b>	VGA 640 x 350 (70Hz) VGA 720 x 400 (70Hz) VGA 640 x 480 (60/72/75Hz) SVGA 800 x 600 (60/72/75Hz) XGA 1024 x 768 (60/70/75Hz) Mac. 832 x 624 (75Hz)	VGA 640 x 350 (70Hz) VGA 720 x 400 (70Hz) VGA 640 x 480 (60/72/75Hz) SVGA 800 x 600 (60/72/75Hz) XGA 1024 x 768 (60/70/75Hz) Mac. 832 x 624 (75Hz)
<b>Max. Resolution</b>	1024 x 768 ppi	1024 x 768 ppi
<b>Contrast Ratio</b>	400	300
<b>Brightness</b>	230	235 cd/m <sup>2</sup>
<b>Response Time</b>	15mS (Rising), 10mS (Falling )	25mS (Rising), 25mS (Falling )
<b>Viewing Angles</b>	+80°C ~ -80°C (L/R), +80°C ~ -80°C (U/D)	+60°C ~ -60°C (L/R), +40°C ~ -60°C (U/D)
<b>Display Colour</b>	16M (dithering)	16M (dithering)
<b>Input Signal</b>		
<b>Video</b>	RGB Analog 0.7V Peak-to-Peak	RGB Analog 0.7V Peak-to-Peak
<b>Sync</b>	TTL Positive or Negative	TTL Positive or Negative
<b>Signal Input Connector</b>	15 Pin Mini D-sub	26 Pin Mini D-sub
<b>On Screen Controls</b>	Power Switch, Menu, Select (up, down), Adjust (+,-)	Power Switch, Menu, Auto-Adjustment, Adjust (Up, -) Adjust (Down, +), Volume
<b>OSD</b>	Auto-Adjustment, Contrast, Brightness, Clock, Phase, H-Position , V-Position, Color Temperature, Load default	Auto-Adjustment, Contrast, Brightness, Clock, Phase, H-Position , V-Position, Color Temperature,
<b>Plug &amp; Play</b>	DDC1/2B	DDC1/2B
<b>Audio System</b>	2W per Channel	(Optional) 2W per Channel
<b>Video in (optional)</b>	Pal/NTSC S-video/ AC connector	Pal/NTSC S-video/ AC connector
<b>Power</b>	Universal 90-240V, 12V/ 35W	Universal 90-240V, 12V/ 35W
<b>Dimensions</b>	404 x 393 x 162 mm	355.5 x 379 x 162 mm
<b>Touch Screen</b>	Optional	Optional
<b>MSR</b>		Optional Easy attachable MSR Module
<b>Weight</b>	8Kg	8Kg
<b>Certification</b>	FCC-B, CE, UL	FCC-B, CE, UL , TUV