

Optional Peripheral:

- MSR Card Reader
- Pole Display
- 32 Key Programmable
- POS Keyboard
- Smart Card Reader
- RFID & 802.11g Wire-less
- Module
- Finger Print Sensor
- Cash Drawer Controller
- Secondary LCD Display
- W/Touch Function
- Dallas Key

Compatible Operating System:

- Microsoft Windows 95/98/NT/2000/XP/XP Embedded
- WEPOS
- DOS
- Linux



DigiTouch - All in One Touch PoS



The DigiTouch is the new innovative all-in-one touch screen PoS system from DigiPoS suitable for Retail, Hospitality, Hotel, Supermarket, Casino, Theme Park etc.

The Ultra Low voltage, energy efficient operation is ideal for the environmentally aware business. The low noise design is suitable for noise-intolerant environments while its compact size and variety of available peripherals delivers a fully flexible system which can be optimised to suit your needs.

The features

- The Ultra Low voltage design delivers the power saving function to render low energy consumption systems
- Low noise design is suitable for noise-intolerant environments, such as pharmacies, museums and SPA resorts
- Compact size increases counter space
- Complies with IP 43 standard. The system is able to operate safely under harsh environments such as pubs, kitchens, and other settings. For fan-less solutions, the dust will not accumulate at the vents.
- Supports VIA C7 1.0GHz (Fanless) / VIA C7 2.0 GHz CPU.
- WEPOS / XPE Solution.
- RoHS compliant.

The options

- MSR, Smart Card Reader, Fingerprint Recognition System, Dallas Key, Pole Display
- Powered USB outputs available
- Touch-screen
- Cable cover
- Secondary LCD display
- Keyboard
- RFID option



DIGITOUCH ULV 1.0/2.0

THE SPECIFICATION

| | |
|------------------------------|---|
| CPU Support | DigiTouch ULV 1.0 Pro: VIA Eden 1 Ghz (fan-less), DigiTouch ULV 2.0 Pro: VIA Eden 2 Ghz (Low RPM) |
| System Core Logic | NB: VIA CN700 SB: VIA VT-8237R+ |
| System RAM Module | DDR-200 Pin RAM socket x 1 (up to 1 GB) |
| Graphics | VIA S3 AGP up to 64MB |
| HDD | 3.5" x 1 |
| Compact Flash Card | Compact Flash Card Socket (Type I / II) x 1 Supported |
| LCD Size | 15in TFT Panel with LVDS Interface |
| Touch Screen | 15in LCD Touch Panel |
| Brightness | 250 cd/m2 |
| Resolution | 1024 x 768 Max |
| Display Function | VIA Dual-view Built-in AGP 8X Shared Memory up to 64MB |
| Screen Adjustment | Brightness & Volume adjust button |
| Serial Port | 6 total. 1 dedicated to Touch, 4 x conventional DB-9, 1 x RJ45 for Customer Display |
| USB Port | 5 total 1 x 12V power USB, 1 x 24V power USB, 2 rear accessible, 1 front accessible |
| PS/2 Port | 1 x combined keyboard & mouse port |
| LAN Port | Realtek RTL-8100CL Ethernet Port on board (10/100 Base-T) |
| Audio Port | Line Out |
| Cash Drawer Control | RJ12 Socket |
| DC Output for | 1 x 24V Hosidan connector, 1 x 12V barrel connector |
| Power Supply | DC 24V / 5A External Power Adapter (120W) |
| Safety | UL / CUL / FCC / CE / VCCI |
| Dimensions | 380mm(L) x 280mm(W) x 360mm(H) |
| Operation Temperature | 0-40 Degrees C |

OPTIONS

| | |
|-------------------------------|--|
| FDD | External USB FDD |
| CD-ROM | External USB CD-ROM / DVD ROM / COMBO |
| Programmable POS K/B | 8 x 4 Matrix Programmable POS K/B with 6 stage Key Switch |
| Magnetic Stripe Reader | 3 Track |
| Smart Card Reader | Smart Card Reader / Writer conforming to ISO 7816 Standard |
| Customer Display | 2 x 20 VFD Customer Display |
| Secondary LCD Display | 12.1in TFT LCD Display |
| Finger Print Sensor | Optical Finger Print Sensor |
| Security ID-Device | Dallas Key (I-Button) |



DigiPoS Store Solutions

Unit 6 Kyalami Crescent, Kyalami Business Park, Kyalami Midrand, South Africa Tel: +27 11 466 4000 Fax: +27 11 466 4038
Offices in Australia, Denmark, Finland, France, Germany, Norway, North America, South Africa, Sweden, Switzerland, Taiwan and UK

www.digipos-solutions.com